



W I M A QUALITY ASSURANCE

CUSTOMER PCN ACKNOWLEDGEMENT FORM

Part: Metallized Polyester (PET) Capacitors

WIMA Type: **WIMA MKS 2/PCM 5mm**
1000pF through 0,22 μ F / 50VDC
1000pF through 6800pF / 63VDC
/ 100VDC
/ 250VDC
/ 400VDC

as well as 10 μ F / 16VDC

and 1000pF through 2200pF / 630VDC 2,5x6,5x7,2/PCM 5
0,22 μ F / 63VDC 2,5x6,5x7,2/PCM 5
0,47 μ F / 50VDC 2,5x6,5x7,2/PCM 5

Change : to be discontinued or modified respectively due to the change of equipment and replaced as of now/as soon as possible (at the end of 2006 latest) by

WIMA MKS 2/PCM 5mm \rightarrow \succ U_R) change of U_R

WIMA MKS 2-XLnew/PCM 5mm
10 μ F /16 VDC) change of type

and 1000pF through 2200pF / 630VDC 3x7,5x7,2/PCM 5)change of dimensions
0,22 μ F / 63VDC 3x7,5x7,2/PCM 5)change of dimensions
0,47 μ F / 50VDC 3x7,5x7,2/PCM 5)change of dimensions

There is no impact on electrical and reliability parameters due to these changes!

We confirm that all WIMA PET capacitors

- are in accordance with data given in the WIMA catalogue 2005/2006
- have been tested and certified according to the IEC generic specification for fixed capacitors for electronic equipment (IEC 60384-1)
- have an encapsulation made of self-extinguishing material according to UL 94V-0
- have been tested 100% for all electrical parameters inclusive dielectric strength

Signature: Roland Wilhelm

Function: Technical Support

Date: September, 2006