



W I M A QUALITY ASSURANCE

CUSTOMER PCN ACKNOWLEDGEMENT FORM

Part: Film and Foil Capacitors with Mixed Dielectric (FKM)

WIMA Type: **WIMA FKM 3/PCM 7.5mm through 15mm**

220pF through 680pF / 100VDC
/ 250VDC
/ 400VDC
/ 630VDC

and

lead diameter PCM 7,5mm B ≥ 4mm Ø 0,7mm
lead diameter PCM 10mm B ≥ 4mm Ø 0,7mm

Change: to be discontinued or modified respectively due to the change of equipment and replaced as of now/as soon as possible (at the end of 2006 latest) by

WIMA FKP 3/PCM 7.5mm through 15mm

220pF through 680pF / 100VDC)change of type
/ 250VDC)change of type
/ 400VDC)change of type
/ 630VDC)change of type

and

lead diameter PCM 7,5mm B ≥ 4mm Ø 0,6mm)change of lead diameter
lead diameter PCM 10mm B ≥ 4mm Ø 0,6mm)change of lead diameter

There is no impact on electrical and reliability parameters due to these changes!

We confirm that all WIMA FKM/PP capacitors

- are in accordance with data given in the WIMA catalogue 2005/2006
- have been tested and certified according to the IEC generic specification for fixed capacitors for electronic equipment (IEC 60384-1)
- have an encapsulation made of self-extinguishing material according to UL 94V-0
- have been tested 100% for all electrical parameters inclusive dielectric strength

Signature: Roland Wilhelm

Function: Technical Support

Date: September, 2006