



W I M A QUALITY ASSURANCE

CUSTOMER PCN ACKNOWLEDGEMENT FORM

Part: Metallized Polypropylene (PP) Capacitors

WIMA Type: **WIMA MKP-X2/PCM 7.5mm through 27.5mm**
lead diameter PCM 7,5mm B \geq 4mm \varnothing 0,7mm
lead diameter PCM 10mm B \geq 4mm \varnothing 0,7mm

Change : to be modified due to the change of equipment and replaced
as of now/as soon as possible (at the end of 2006 latest)by

WIMA MKP-X2/PCM 7.5mm through 27.5mm
lead diameter PCM 7,5mm B \geq 4mm \varnothing 0,6mm)change of lead diameter
lead diameter PCM 10mm B \geq 4mm \varnothing 0,6mm)change of lead diameter

There is no impact on electrical and reliability parameters due to these changes!

We confirm that all WIMA PP capacitors

- are in accordance with data given in the WIMA catalogue 2005/2006
- have been tested and certified according to the IEC generic specification for fixed capacitors for electronic equipment (IEC 60384-14/2)
- have an encapsulation made of self-extinguishing material according to UL 94V-0
- have been tested 100% for all electrical parameters inclusive dielectric strength

Signature: Roland Wilhelm

Function: Technical Support

Date: September, 2006